

Lighting systems - corridor illuminators - LED panel

With our lighting solutions we respond to the specific requirements of our customers. HT lighting systems form the perfect supplement to the modular wall and ceiling system. Ultra-flat construction comprising an LED panel with an all-round frame

(colour silver). Homogenous opal-look LED light. Installation on the ceiling panel using comfortable magnetic catches, including a safety cord.

Technical data

Dimensions in mm	225 x 225 x 25	595 x 595 x 32	620 x 620 x 8	1195 x 295 x 8
Power (at 700 mA)	18 W	27 W	40 W	40 W
Luminous flux (at 700 mA)	1580 lm	4000 lm	3900 lm	3900 lm
Colour temperature	3000 K / 4000 K	4000 K	3000 K / 4000 K / 5700 K	3000 K / 4000 K / 5700 K
Colour rendering index	> 80	> 82	> 92	> 92

Components

LED panel	homogeneous opal-look LED light
Frame	standard: colour silver optional: colour white like RAL 9016 (only for a minimum order quantity of 50 pcs)
LED-Power supply unit CC950 mA 38 W	input voltage 220 - 240 V AC output voltage 33 - 40 V DC
Installation	on the ceiling panel using a magnetic catch and safety cord

Special fittings

LED-Power supply unit CC 1050 mA 40W	3-step dimmable output voltage: 19 - 38 V DC
---	--